

WB-521 Series

Heavy Duty Weigh Beams



- **Quick Set-up**– This highly portable scale system is designed with simplicity in mind. In just a few minutes the entire scale is setup and ready to weigh.
- **Two Weigh Beams**– The system includes two Weigh Beams with built in carry handles. Each Weigh Beam has 4 m /13' of load cell cable with quick connectors.
- **Display**– Easy-to-read LCD with adjustable brightness
- **Indicator Rating:** IP65 rated waterproof stainless steel enclosed indicator and stainless steel mounting bracket
- **Common Applications**– Fully portable scale system is ideal for weighing pallets, long loads and installations under conveyors, tanks and hoppers. Also suitable for long lengths of pipe or other difficult to handle materials.
- **Internal Filtering:** Adjustable filter setting to reduce environmental vibration noise for rapid setting and quick measurements
- **Pre-Calibrated**



WB-521 Series Weigh Beams

Features

- Simple to set-up and easy-to-use design
- Equipped with IP65 rated waterproof stainless steel enclosed indicator and stainless steel mounting bracket
- Easy-to-read LCD display
- Tough mild steel weigh beams for heavy industrial use
- Adjustable distance between beams according to the size of the load
- Four broad adjustable rubber feet for maximum stability
- Each beam is only 16.5 kg /36 lb light enough to be carried by one person
- Programmable hold, print, accumulation and check weighing functions
- Geography auto-compensation for local gravity effects to avoid initial calibration with test weights
- Advanced weigh fine-tune feature to make simple calibration convenient
- Adjustable filter settings to reduce environmental vibration noise for rapid setting and quick measurements

Specifications

- Capacity:** 5000 kg x 0.5 kg / 10,000 lb x 1 lb
- Construction:** Mild steel beam with stainless steel housing indicator
- Load Cell:** Four 350 ohm load cells with an output of 2mV/V
- Unit of Measure:** kg, lb, lb:oz, PCS, %
- Display:** 7 digits, 7 segment 25 mm (1") LCD
- Real Clock:** Built-in nonvolatile real time & date
- Function Keys:** N/G, Hold, Print, Unit, Tare, On/Off/Zero

Specifications

- Zero Range:** Selectable up to full capacity
- Tare Range:** 100% subtractive
- Static Overload Capacity:** 200%
- Calibration:** Front panel access with Geography auto compensation features
- Serial Port:** Full-duplex RS-232 interface, half-duplex RS-485
- Power:** Internal PSU and 6V 4Ah rechargeable battery
- Approximate Battery Life:** 48 hr
- Operating Temperature:** -10° C to 40° C / 14° F to 104° F
- Beam Dimension:**
1200 mm (L) X 100 mm (W) x 60 mm (H)
47.24" L x 3.94" W x 2.36" H
- Beam to Beam Cable Length:** 4 m / 13'
- Indicator to Beam Cable Length:** 4 m / 13'
- Indicator Dimension:**
262 mm (L) x 215 mm (W) x 94 mm (H)
10.3" L x 8.5" W x 3.7" H
- Packing Dimension:**
1335 mm (L) x 535 mm (W) x 250 mm (H)
53" L x 21" W x 10" H
- Shipping Weight:** 39.5 kg / 87 lb
- Product Code:**
816965005635: UK - 5000 kg

Options



a division of Avery Weigh-Tronix, LLC

Midland Pallet Trucks, Unit 33, Second Avenue,
Pensnett Trading Estate, Kingswinford, West Midlands, DY6 7UG

