

EPT20A-BR HEAVY DUTY

LITHIUM PALLET TRUCK WITH LOAD BACK REST

24 HOURS
BUILT TO WORK



midland
pallet trucks

Electric Pallet Truck with Load Backrest

Designed for safer handling of taller or more unstable loads, this electric pallet truck is fitted with a robust load backrest to help keep goods securely positioned during transport.

The load backrest is manufactured from strong welded steel, providing a durable barrier behind the forks. This helps support tall loads while also offering additional protection for the operator during movement and positioning.

For added load security, the truck is equipped with an integral securing strap and locking mechanism. This helps give the operator confidence that the load will remain firmly located on the truck during use.

The load backrest measures 1.5m high from the top of the forks, making it ideal for applications where palletised goods, stacked items or taller loads require additional support.

Key Features

- Strong welded steel load backrest
- Helps support tall or unstable loads
- Provides added operator protection
- Integral securing strap with lock
- Backrest height: 1.5m from top of forks


Suitable for safer internal handling of taller palletised goods

SMART **POWERFUL** DURABLE

BUILT TO
WORK
24
HOURS

SMART SIZE

ALMOST SAME



LIGHT WEIGHT




ONLY 125kgs

80 kgs

EFFICIENCY


3 Times Higher Than Manual Pallet Truck



VS



EASY MAINTENANCE



LIFETIME


3 Times Longer Than Manual Pallet Truck



1 PC

VS

3 PCS



6%

HIGH RETURN OF INVESTMENT

Safety

PRODUCTIVE

1 MONTH COST
RECOVERY

Optimize
your operations
SAVE LABOUR
Brake any time anywhere

Release manpower

midland
pallet trucks

Powerful With High Gradeability



Unique brushless technology

Brushless motor, powerful and maintenance free.
Leading in the industry.



1000W power
Brushless motor
Maintenance free



Powered traveling



Powered lifting & lowering

Maintenance free

For brushed motor, carbon brush needs to be replaced every 12 or 18 months.
For EPT15H, no need to replace carbon brush.
Maintenance-free, saving maintenance time and cost.

Powerful with high gradeability

To easily move 1.5 ton or 2 ton over the slopes at warehouse entrances.





Traveling speed



UNLADEN 4.5km/h



LADEN 4km/h



Gradeability



midland
pallet trucks

Non-stop Working

6s to replace battery

Maintenance-free lithium battery
It takes only 6s to replace battery.
With a spare battery, the unit can keep working 24 hours.

Ensured battery safety

Safe and reliable, no fire, no explosion.
Complying with IEC, UL global standard certification requirements, ensuring the safety of user property.

- Long service life: lithium battery with a long service life.
- High safety performance: it adopts soft package battery technology, built-in protection board and multiple protection to eliminate overcharge and overdischarge.
- Maintenance free: no need to add water.

Compact and durable

Solid build, no breaking

Chassis made by solid materials, no bending, no deformation.
Reinforced rocker arm, push rod, wheel frame and support seat.
No plastic part, less damage.

Most compact unit with same lifting capacity

Suitable for small workplaces such as compact workshops, trucks or vans, tail lifts or elevators.
EPT15H has the smallest turning radius among similar products.

Integral forks, no splicing

The forks are uniquely designed, easy to handle European pallets, American pallets and plastic pallets.
Solid fork with no deformation, far more durable than other brands of the same category.

Short charging time Charge and use freely

Quick charging: 2 hours to fully charge the battery using the optional Quick charger.



Fork thickness

4mm

V-block thickness

5mm

Top cap thickness

6mm


**Solid build
No breaking**



Intelligent Control

When you're moving heavy loads in tight spaces, maneuverability and controllability are critical to ensure safety, productivity and comfort.

The core concept of MIDLAND products is to make your job easier. With the ergonomically designed handle, EPT15H is easy to operate, reduces fatigue and improves work efficiency. Compared to other brands, users prefer to use MIDLAND EPT series.




Operator Preferred

Turtle Speed

01


Horn Remains Pressed & Forward 2 times



Up-Right Drive

02


Reverse Button & Forward Throttle Remain Pressed Power On



Engineering Mode (Brake Release)

03

Horn Remains Pressed Power On



- ⚠ In up-right drive mode, vehicle will move when handle is operated at any position. Please avoid misoperation.
- ⚠ Brake release mode is only for emergencies, not allowed for vehicle with normal conditions.

Comfortable Operation

Easy to operate
Ergonomic handle, comfortable to use.

Leading Technology

CanBus technology is applied on this entry-level electric pallet truck.

Fast And Slow Speed

To match different levels of operator experience, and varied work environments.

Up-right Drive Mode

Convenient to operate in vans, on tail lifts, or inside elevators.

Engineering Mode

When the unit breaks down, it can be moved away manually.



- Recharge alert
- Hour meter
- Powered traveling
- Powered lifting & lowering
- Error code display
- Emergency stop button
- Horn

Slope anti-sliding design

Easy parking on slopes, preventing accidental backing of the machine.

Easy Maintenance

EPT series utilizes MIDLAND's integrated diagnostics, error code display and MIDLAND's original service mini-program to facilitate quick problem resolution.

Easy parts replacement


The unique design makes disassembly and assembly simple, reducing machine downtime and operating costs.

- **1 minute**
Replace the drive wheel
- **1 minute**
Replace the handle
- **2 minutes**
Remove the controller
- **3 minutes**
Remove the motor




Error Code Display

Quickly identify the fault during operation.



Specialized service website & mini-program

Users can identify the fault based on the online troubleshooting videos. No limit on time, no limit on location. Easy access to the most professional solution to all possible truck failures.




Professional after-sales support

Specialist guidance is a phone call away.

Ready to Handle Multiple Jobs

With its unique design, EPT series is powerful and maneuverable to meet the application in a wide range of working conditions.



Warehouses/Logistics center



Truck tail lift



Supermarket

Pallet trucks are a necessary investment. Choosing the wrong machine could cause loss in productivity, high cost of machine downtime, unhappy workers, and overall, increased running costs. Choosing EPT series will reward you with long-term value.

MIDLAND EPT Series

- **Powerful**
- **Durable**
- **Easy maintenance**
- **Low use cost**
- **High return on investment**

Basic Configuration

EPT20-A

Horn
Emergency reverse button
Forward/reverse butterfly switch
Lifting / Lowering

LCD Screen

- Battery indicator with hour meter
- Error code display
- Recharge alert



Multi-function Handle
(Full Electric)



Tandem/Single PU wheel



Lithium Battery



Protection cover
Protect the drive motor,
Anti-foot stamping



Intelligent charger


EPT20-A



Electric lifting/lowering

Dimensions


midland
pallet trucks



Specifications

MODEL			PPT20H	EPT15H	EPT20-A	EPT15H-65L
CHARACTERISTICS						
1.1	Drive		Electric	Electric	Electric	Electric
1.2	Operator type		Pedestrian	Pedestrian	Pedestrian	Pedestrian
1.3	Load capacity/rated load	Q kg	2000	1500	2000	1500
1.4	Load centre	C mm	600	600	600	600
1.5	Height, fork lowered	h ₁₃ mm	82 ± 2	82 ± 2	82 ± 2	65 ± 2
1.6	Wheelbase	y mm	1197/1267	1197/1267	1197/1267	1197/1267
1.7	Wheel		PU	PU	PU	PU
1.8	Wheel size, front	mm	140*55	140*55	140*55	140*55
1.9	Wheel size, rear	mm	80*93 (Single Wheel)	80*93 (Single Wheel)	80*70 (Tandem)	60*93 (Single Wheel)
		mm	80*70 (Tandem)	80*70 (Tandem)		60*70 (Tandem)
1.10	Wheels, number front/rear (x = drive wheels)		1x+2/4	1x+2/4	1x+2/4	1x+2/4
1.11	Lift	h ₃ mm	195	195	195	100
1.12	Height of tiller in drive position, min./max.	h ₁₄ mm	740/1220	735/1170	735/1170	735/1170
1.13	Overall length	L ₁ mm	1552/1622	1552/1622	1552	1566/1636
1.14	Fork Length	L mm	1150/1220	1150/1220	1150	1150/1220
1.15	Overall width	b ₁ mm	550/685	550/685	550	550/685
1.16	Fork dimensions	mm	58/160/1150(1220)	58/160/1150(1220)	58/160/1150	45/160/1150(1220)
1.17	Overall fork-arms Width	b ₅ mm	550/685	550/685	550	550/685
1.18	Ground clearance, centre of wheelbase	m ₂ mm	22/137(24/139)	22/137(24/139)	22/137	16.5/116.5(17.2/117.2)
1.19	Aisle width for pallets 1000x1200 crossways	A _{st} mm	2155/2226	2155/2226	2155/2226	2155/2226
1.20	Aisle width for pallets 800x1200 lengthways	A _{st} mm	2024/2064	2024/2064	2024/2064	2024/2064
1.21	Turning radius	Wa mm	1353/1426	1353/1426	1353	1353/1426
PERFORMANCE						
2.1	Travel speed, laden/unladen	km/h	4.0/4.5	4.0/4.5	4.0/4.5	4.0/4.5
2.2	Lifting speed, laden/unladen	mm/s	/	18/23	18/23	18/23
2.3	Lowering speed, laden/unladen	mm/s	/	56/46	56/46	56/46
2.4	Max. gradeability, laden/unladen	%	6%/20%	6%/20%	6%/20%	6%/20%
2.5	Drive motor	kW	DC 1.0 Brushless	DC 0.75 Brushless	DC 1.0 Brushless	DC 0.75 Brushless
2.6	Lift motor	kW	Hydraulic	DC 0.8	DC 0.8	DC 0.8
BATTERY						
3.1	Battery voltage/nominal capacity	V/Ah	48V/10Ah	48V/10Ah	48V/10Ah	48V/10Ah
3.2	Traveling brake		Regenerate	Regenerate	Regenerate	Regenerate
3.3	Brake		Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
3.4	Sound level at the driver's ear according to EN 12053	A	< 70dB	< 70dB	< 70dB	< 70dB
3.5	Service weight including battery	kg	117/123.5	116.5/123	119/125.5	116.5/123

| MAKE
YOUR JOB
EASIER!



midland
pallet trucks

Email: sales@midlandpallettrucks.com

Phone: 01384 841440

Web: <http://www.midlandpallettrucks.com>

Add: Midland Pallet Trucks, Building 33 Second Avenue,
Pensnett Trading Estate, Kingswinford, DY6 7UG